REPAIR

All repair work shall be performed by the manufacturer. All other work or modifications will void the warranty and releases CMC Rescue, Inc. from all liability and responsibility as the manufacturer.

SAMPLE INSPECTION AND MAINTENANCE LOG

The sample log suggests records that should be maintained by the purchaser or user of rescue equipment.

Equipment Inspection and Maintenance Log			
Item # Date in Service Brand/Model Strength			
Date	How Used or Maintained	Comments	Name

CMC Rescue, Inc.

6740 Cortona Drive, Goleta CA 93117 USA 805-562-9120 / 800-235-5741 cmcrescue.com

ISO 9001 Certified

©2016 CMC Rescue, Inc. Control No. 202690.00.042116

The **SkySaddle** provides additional comfort when you need to spend an extended amount of time sitting in your harness. The saddle attaches to the front D-Ring of CMC Rescue and most other class III harnesses. Side adjustments allow the wearer to transfer as much or as little weight from the harness to the saddle as desired. As a result, the sitting position can be varied to minimize pressure points, extending the comfortable working time.

USER INFORMATION

User Information shall be provided to the user of the product. CMC Rescue recommends separating the User Information from the equipment and retaining the information in a permanent record. CMC also recommends making a copy of the information to keep with the equipment and that the information should be referred to before and after each use.

INSPECTION

Inspect the equipment according to your department's policy for inspecting life safety equipment. The equipment should be thoroughly inspected after each use by an inspector that meets your organization's training standard for inspection of life safety equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should inspect the equipment before each use.

When inspecting the equipment, check the webbing and rope for cuts, worn or frayed areas, broken fibers, soft or hard spots, discoloration, or melted fibers. Check the stitching for pulled threads, abrasion, or breaks. Check the hardware for damage, sharp edges, and improper operation. If any of the above is noted, or if the equipment has been subjected to shock loads, fall loads, or abuse other than normal use, remove the equipment from service and destroy it. If there is any doubt about the serviceability of the equipment, remove the equipment from service and destroy it.

IMPORTANT INFORMATION - PLEASE READ AND SAVE



$SkySaddle^{^{TM}}$

Made in USA

of US and foreign components

PRODUCT LABEL

- SERIOUS INJURY OR DEATH MAY RESULT FROM THE IMPROPER USE OF THIS EQUIPMENT.
- THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.
- DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PRIOR TRAINING.
- THOROUGHLY READ AND UNDERSTAND ALL LABELS AND INSTRUCTIONS BEFORE USE.
- USE, INSPECT AND REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

The service life of equipment used for rescue depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

USE

Connect the straps of the saddle to the waist D-Ring. Adjust the saddle to the desired position. While the saddle can be adjusted while under suspension, it is much easier to do so when not under load. The sewn loops on the bottom and sides of the saddle can be used to secure hand tools while working.

Warning: This equipment is designed primarily for rope access work and is to be used only by professionally trained individuals. To prevent serious injury or death, the Sky Saddle shall be connected to the user's harness and not independently into the system. The saddle is designed to function as an integral component of a full body harness and is NOT a Boatswain's Chair and is NOT to be considered standalone personal protective equipment (PPE).

CARRYING, MAINTENANCE & STORAGE

During use, carrying and storage keep the equipment away from acids, alkalis, exhaust emissions, rust and strong chemicals. Do not expose the equipment to flame or high temperatures. Carry the equipment where it will be protected as the equipment could melt or burn and fail if exposed to flame or high temperatures.

If the equipment becomes soiled, it can be washed in cold water with a mild detergent. CMC Rescue recommends the use of LifeLine Cleaner. Dry out of direct sunlight. Do not dry in an automatic dryer. Store in a cool, dry location. Do not store where the equipment may be exposed to moist air, particularly where dissimilar metals are stored together.