# **Darley**

# FAST ATTACK SKIDS CUSTOMIZABLE DROP-IN SKID UNITS

### **FAST ATTACK 1**

**APPLICATIONS** 

The Fast Attack 1 comes with a 13 hp Davey two-stage pump with a 200 gallon Pro Poly tank and Hannay electric booster reel with 100' of 1" hose.

Wildland/quick attack fire suppression, skid unit, brush fires, water transfer

### **DIMENSIONS & WEIGHT**

**STANDARD FEATURES** 

94"L x 48"W x 42"H, 700 lbs. (318 kg)

#### Fast Attack 1 With Options





AMILY OWNED

- 13 hp twin impeller Davey with Briggs & Stratton engine
- 200 gallon Pro Poly tank

- 1" tank recirculation
- $1^{1}/_{2}$ " tank to pump and discharge
- Multiple configurations
- C-channel bases
- Solid pump performance for wildland firefighting
- Fast delivery
- Made in the USA

# **OPTIONS**

- Water/foam nozzle packages for N.A.F.S. Poly hose tray
- Roller and spool hose guide
- Built-in 10 gallon foam cell
- ATP Foam Flurry™ proportioner
- 1<sup>1</sup>/<sub>2</sub>" Mattydale swivel
- Work light

- Additional 2<sup>1</sup>/<sub>2</sub>" discharge
- Custom tank sizes

Additional custom options available, contact Darley for details.

# PERFORMANCE

### AK305

120 gpm (454 L/M) @ 40 psi (2.8 bar) 95 gpm (360 L/M) @ 108 psi (7.4 bar) 20 gpm (76 L/M) @ 146 psi (10.1 bar)



# F4000 Hannay electric rewind reel 100' of 1" booster hose

- •

FAST ATTACK

- All stainless steel piping and manifold ٠

- Self priming up to 19'
- 2<sup>1</sup>/<sub>2</sub>" NST suction adapter

# **Darley**<sup>®</sup>



With Options





The Fast Attack 2 has the same tank and reel as the Fast Attack 1 but standardizes on our gear-driven or direct-drive Darley pump coupled to an 18 hp engine with control panel.

### **DIMENSIONS & WEIGHT**

94"L x 48"W x 42"H, 900 lbs. (409 kg)

### APPLICATIONS

**FAST ATTACK 2** 

Wildland/quick attack fire suppression, skid unit, brush fires, water transfer

### **STANDARD FEATURES**

- 21 hp Honda Engine
- All stainless steel piping and manifold •
- 200 gallon Pro Poly tank •
- F4000 Hannay electric rewind reel •
- 100' of 1" booster hose
- Self priming up to 19' •
- 2<sup>1</sup>/<sub>2</sub>" NST suction adapter
- 1" tank recirculation

- $1^{1/2}$ " tank to pump and discharge
- Exhaust primer •
- Multiple configurations •
- C-channel bases
- Solid pump performance for wildland firefighting
- Fast delivery
- Made in the USA

### **OPTIONS**

- Water/foam nozzle packages for N.A.F.S. Poly hose tray
- Roller and spool hose guide
- Built-in 10 gallon foam cell •
- ATP Foam Flurry™ proportioner •
- 1<sup>1</sup>/<sub>2</sub>" Mattydale swivel
- Work light

- Additional 2<sup>1</sup>/<sub>2</sub>" discharge
- Custom tank sizes
- Additional pump options, diesel or gas Additional custom options available, contact Darley for details.

### PERFORMANCE

### 1.5AGE21H

120 gpm (454 L/M) @ 155 psi (10.7 bar) 75 gpm (284 L/M) @ 230 psi (15.9 bar) 35 gpm (95 L/M) @ 300 psi (21.7 bar)

#### 2BE21H

380 gpm (1438 L/M) @ 25 psi (1.7 bar) 150 gpm (568 L/M) @ 115 psi (7.9 bar) 100 gpm (378 L/M) @ 135 psi (9.3 bar)

