



3415

Right Angle Light

The most versatile intrinsically safe work light in the world.

The 3415 is the ultimate safety certified compact work light. The Class I II III Division 1 certifications provide the security needed for most hazardous locations. The 3415 is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed.

The Pelican 3415- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.


- 3 modes: Spot, Flood or Both
- Articulating Light Head
- Attached clip
- Class I, Class II, Class III – Division 1 Safety Certified
- Security Lanyard



MATERIALS

| | |
|--------------------------------|---|
| Body | ABS |
| O-Ring | NBR |
| Lens | Polycarbonate (PC) |
| Shroud | ABS |
| Clip | ABS |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze / Brass Nickel Plate |

COLORS

-  High Visibility Yellow

LIGHT SPECS

| | |
|----------------------------|-----|
| Lamp Type | LED |
| Lamp Secondary Type | LED |

POWER

| | |
|-------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Volts | 4.5v |

WEIGHT






| | |
|---------------------------------|-----------------|
| Weight With Batteries | 9.0 oz (255 gr) |
| Weight Without Batteries | 6.6 oz (187 gr) |

SWITCH

| | |
|--------------------|-------------|
| Switch Type | Push Button |
| Light Modes | High |

CERTIFICATIONS

- Class I, Division 1
- Class II, Division 1
- Class III, Division 1
- IECEx ia

| FL1 STANDARD | SPOT / FLOOD | FLOOD | SPOT |
|--|---------------|---------------|---------------|
|  | 336 LUMENS | 177 LUMENS | 186 LUMENS |
|  | 6h 0mins | 15h 0mins | 14h 0mins |
|  | 133m | 37m | 135m |
|  | 4418cd | 336cd | 4544cd |
|  | IPX8 (1m) | | |

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-13-18