

# SHELBY SPECIALTY GLOVES SHELBY FIREWALL ARFF GLOVE

## 5200 & 5200G

MA 2020

**Specifications:**

**Outer Shell:** 7 oz. Aluminized PBI/Kevlar® Knit .025 in. thick (.063 cm) Flexible Pleat on Back of Hand.

**Thermal Liner:** Primary Liner: Defender SL2 Camouflage thermal. Secondary Liner: Direct Grip fabric.

**Protective Barrier:** Crosstech PTFE insert fully bonded to Defender SL2 Camouflage thermal lining.

**Grip Patches:** 3.0 – 3.50 oz. Black Split Cowhide on palm side.

**Wristlet:** 10.5 oz. per yard, double ply black Nomex®, 4 inch length. Not on model 5200G.

**Donning Pull:** 3" x 3 ½" Round Leather Pull, sewn to wristlet & glove body.

**Thread:** Sewn with high burst strength Kevlar® (30/6) lock stitch, 8-10 stitches per inch.

**Hanger Loop:** ¼" fire retardant, split cowhide hanger loop.

**Label:** Label shall be Permanently Attached to each glove & certifies the glove meets or exceeds the requirements of the latest NFPA standards (1971, Standard on Protective Ensemble for Proximity Fire Fighting). Label shall be durable & include the following information: name or designation of manufacture; model; name or style number; lot or serial number; size; patent numbers; cleaning & care instructions. Label to be sewn to inside of glove.

**Origin:** Made in U.S.A.

**Sizes:**

XXS	XS	S	M	L	XL	J		
64N	70N	70W	76N	76W	82N	82W		

**Design & Construction:**

Glove shall be a gunn cut pattern with wing thumb construction. Glove front, back and between fingers is aluminized PBI/Kevlar® material. Leather grip patches applied to palm, thumb and fingers on the palm side. Glove is oversized with expandable pleat, allowing better flex and back of hand insulative airspace.

Glove is constructed, tested and labeled in accordance with the NFPA Standard on Protective Ensemble for Proximity Fire Fighting, NFPA 1971, 2018 Edition. The glove is certified by the Safety Equipment Institute (SEI).

**MEETS TRADE AGREEMENT COMPLIANCE AND BERRY COMPLIANCE.**