SHARK II VENTILATION CHAINSAW









Carbide Tipped Rescue Chain

Specifically designed for Fire Department use, outlasts up to 10 regular chains and stays sharp up to 25 times longer.

Durable Reversable Steel Bar

You have 3 choices to choose from: 16" 54 Drive link Bar, a 20" 64 Drive link Bar for our legacy SHARK owners (this model is the same as our pre 2020 SHARK saws) or our NEW 20" 66 Drive Link Bar. This new 20" 66 Drive Link Bar is the same size as other brand saws making it easy for spare parts management. With this new 20" 66 DL Bar, our SHARK saw will use the same size chain as other brands. All SHARK bars are slotted to fit our CDA-80 depth adjuster and are reversable hardened steel bars for extended life.

CDA-80 Adjustable Depth Adjuster

Control cutting depth from 2" to 10" when plunge cutting. Easy, fast removal when full length of bar is needed.

Adjustable Flow Oil Pump

Keeps chain properly lubricated in diverse conditions with no oil flow at idle.



NEW X-Torq® Engine

Provides peak performance even under heavy loads with 12% higher cutting capacity all while delivering lower fuel consumption and reduced exhaust emission levels.

AutoTune

No time spent on carburetor adjustments as the AutoTune Carburetor compensates for different fuels, altitude, humidity, temperature and clogged air filter automatically providing optimal engine performance.

State-of-the-art filtration system

Air Injection filters out 98% of incoming dust prior to reaching the heavy-duty air filter for longer life and better filtration.



Flip up tank caps

Easy to open and secure firmly, even when wearing thick winter gloves.

Visible fuel level

Easy to check fuel level with transparent fuel indicator.

TECHNICAL SPECIFICATIONS

MODEL	SHARK II - 16" - 54DL	SHARK II - 20" 64DL	SHARK II - 20" 66DL	SHARK III - 16" - 54DL	SHARK III - 16" - 64DL	SHARK III - 16" - 66DL
PART NO.	TS2-57216	TS2-5722064	T\$2-5722066	TS3-39016	TS3-3902064	TS3-3902066
MANUFACTURER	HUSQVARNA®					
	572 XP	572 XP	572 XP	390 XP	390 XP	390 XP
POWER HEAD POWER OUTPUT	5.8hp / 4.3kw	5.8hp / 4.3kw	5.8hp / 4.3kw	6.5hp / 4.8kw	6.5hp / 4.8kw	6.5hp / 4.8kw
DISPLACEMENT	4.3ci / 70.6cc	4.3ci / 70.6cc	4.3ci / 70.6cc	5.37ci / 88cc	5.37ci / 88cc	5.37ci / 88cc
DRIVE LINKS	54 DRIVE LINKS	64 DRIVE LINKS	66 DRIVE LINKS	54 DRIVE LINKS	64 DRIVE LINKS	66 DRIVE LINKS
TYPE	HIGH IMPACT CARBIDE TIPPED CHAIN					
CUTTER TYPE	CARBIDE FLAT 25° - DUAL RAKER					
PITCH	0.404 inch					
GAUGE	0.063 inch					
TYPE	HARDENED STEEL					
DEPTH GAUGE READY	YES - SLOTTED FOR CDA-80 DEPTH GAUGE					
NOSE TYPE	SPROCKET WITH SEALED BEARING					
DURABILITY	HARDENED STEEL - REVERSABLE FOR EXTENDED LIFE 0.063 inch					
GAUGE	40.4/01	22.7/20			22.7/20	2211
LENGTH (NOT MOUNTED)	18-1/2"	22-3/8"	23"	18-1/2"	22-3/8"	23"
INCLUDED	YES					
TYPE ATTACHMENT TYPE MATERIAL	CDA-80					
ATTACHMENT TYPE	OPEN — SLOT MOUNTED — EASY ONE HAND ON/OFF					
MATERIAL	ALUMINUM					
DEPTH ADJUSTMENT	2" to 9" Apx.	2" to 10" Apx.	2" to 9" Apx.	2" to 9" Apx.	2" to 10" Apx.	2" to 9" Apx.
WEIGHT	20.2 lbs / 9.2 kg	20.9 lbs / 9.5 kg	21.1 lbs / 10.9 kg	22.2 lbs / 10.1 kg	22.9 lbs / 10.4 kg	23 lbs / 10.4 kg
LENGTH	32.5 in / 826 mm	36.5 in / 927 mm	37.5 in / 953 mm	32.5 in / 826 mm	36.5 in / 927 mm	37.5 in / 953 mm
LENGTH	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm
HEIGHT	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	13.2 in / 335 mm	13.2 in / 335 mm	13.2 in / 335 mm
FULL WRAP HANDLE	YES					
SCRENCH TOOL HOLDER	YES					
"D" STARTER HANDLE	YES					
X-TORQ POWER	YES					
AUTOTUNE CARB.	YES NO					
SPARK PLUG	CHAMPION RCJ7Y / NGK BPMR7A					
FUEL CAPACITY	0.185 gal / 0.70 L 0.238 gal / 0.90 L					
FUEL TYPE	87 OCTANE GASOLINE OR HIGHER - 2 STROKE OIL MIXED 50:1					
BAR OIL CAPACITY	0.425 qt / 0.40 L			0.53 qt / 0.50 L		
NOISE LEVEL	AT OPERATOR 105 db AT OPERATOR 107 db					
	1 YEAR					



TEAM EQUIPMENT, INC.6620 Orchid Lake Road
New Port Richey, FL. 34653
727-848-2424 | 800-367-9054 www.teamequipment.com